

Radio Equipment Directive-Health  
For  
Shandong USR IOT Technology Limited

Serial to GPRS Module

Model No.: USR-GM3, USR-GM3s, USR-GPRS232-7S3, USR-GPRS232-730,  
USR-GPRS232-702, USR-GPRS232-703, USR-GPRS232-704,  
USR-GPRS232-705, USR-GPRS232-732, USR-GPRS232-734

Prepared for       : Shandong USR IOT Technology Limited  
Address             : Floor 11, Building 1, No. 1166 Xinluo Street, Gaoxin Qu,  
250101, Jinan, Shandong, China

Prepared By       : Shenzhen Anbotek Compliance Laboratory Limited  
Address             : 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road,  
Nanshan District, Shenzhen, Guangdong, China  
Tel: (86) 755-26066544  
Fax: (86) 755-26014772

Report No.         : R0116051022H  
Date of Test        : Jun. 02~ Sept. 27, 2016  
Date of Report      : Sept. 30, 2016

## TABLE OF CONTENT

Description	Page
<b>1. GENERAL INFORMATION.....</b>	<b>4</b>
1.1 Description of Device (EUT).....	4
1.2 Description of Test Facility.....	5
1.3 Measurement Uncertainty.....	5
<b>2. GENERAL PRODUCT INFORMATION.....</b>	<b>6</b>
2.1 Basic Restriction.....	6
2.2 Table for Filed Antenna.....	6
<b>3. TEST RESULT.....</b>	<b>7</b>
3.1 EMF Exposure Measurement.....	7
3.2 Detailed results.....	11

## TEST REPORT DESCRIPTION

Applicant : Shandong USR IOT Technology Limited  
Manufacturer : Shandong USR IOT Technology Limited  
EUT : Serial to GPRS Module  
Model No. : USR-GM3, USR-GM3s, USR-GPRS232-7S3, USR-GPRS232-730,  
USR-GPRS232-702, USR-GPRS232-703, USR-GPRS232-704,  
USR-GPRS232-705, USR-GPRS232-732, USR-GPRS232-734  
Serial No. : N.A.  
Trade Mark :   
Rating : DC 3.8V, 750mA


Test Procedure Used:  
EN 62311: 2008

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report shows the EUT to be technically compliant with the EN 62311:2008 requirements. The test results are contained in this report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full responsibility for the accuracy and completeness of these tests.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited..

Date of Test : Jun. 02~ Sept. 27, 2016

Prepared by :



(Engineer / Baron Wen)

Reviewer :

(Project Manager/Amy Ding)

Approved & Authorized Signer :

(Manager/Tom Chen)

## 1. GENERAL INFORMATION

### 1.1 Description of Device (EUT)

EUT	: Serial to GPRS Module
Model Number	: USR-GM3, USR-GM3s, USR-GPRS232-7S3, USR-GPRS232-730, USR-GPRS232-702, USR-GPRS232-703, USR-GPRS232-704, USR-GPRS232-705, USR-GPRS232-732, USR-GPRS232-734 (Note: All samples are the same except the model number and colour, so we prepare “USR-GM3” for test only.)
Rated Power Supply Voltage	: AC 230V, 50Hz for adapter
Adapter	: Model No.: DQS151-120100-VC Input: AC 100-240V, 50/60Hz, 0.4A Max Output: DC 12.0V, 1.0A
Frequency	: GSM900: 880.2-914.8MHz(TX), 925.2-959.8MHz(RX) DCS1800: 1710.2-1784.8MHz (TX), 1805.2-1879.8MHz (RX)
Test Modulation	: GSM/GPRS: GMSK
Antenna Gain	: GSM 900: 2.5 dBi GSM 1800: 2.5 dBi
GPRS Multislot Class	: 8/10/12
Applicant Address	: Shandong USR IOT Technology Limited Floor 11, Building 1, No. 1166 Xinluo Street, Gaoxin Qu, 250101, Jinan, Shandong, China
Manufacturer Address	: Shandong USR IOT Technology Limited Floor 11, Building 1, No. 1166 Xinluo Street, Gaoxin Qu, 250101, Jinan, Shandong, China
Factory Address	: Shandong USR IOT Technology Limited Floor 11, Building 1, No. 1166 Xinluo Street, Gaoxin Qu, 250101, Jinan, Shandong, China
Date of receiver	: Jun. 02, 2016
Date of Test	: Jun. 02~ Sept. 27, 2016

## 1.2 Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

### **FCC-Registration No.: 752021**

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 752021, July 06, 2016.

### **IC-Registration No.: 8058A-1**

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration 8058A, Jun. 13, 2016.

### **CNAS - LAB Code: L3503**

Shenzhen Anbotek Compliance Laboratory Limited., Laboratory has been assessed and in compliance with CNAS/CL01: 2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing Laboratories.

### **Test Location**

All Emissions tests were performed  
Shenzhen Anbotek Compliance Laboratory Limited. at 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan District, Shenzhen, Guangdong, China

## 1.3 Measurement Uncertainty

Radiation Uncertainty : Ur = 4.1 dB (Horizontal)  
Ur = 4.3 dB (Vertical)

Conduction Uncertainty : Uc = 3.4 dB

## 2. GENERAL PRODUCT INFORMATION

### 2.1 Basic Restriction

The essential requirements of Directive 99/5/EC in the article 3.1(a) and the limits must be taken from Council Recommendation 99/519/EC for General Population or form the ICNIRP Guidelines for Occupational Exposure. EN 50371:2002 Generic standard to demonstrate the compliance of low power electronic and electrical apparatus with the basic restrictions related to human exposure to electromagnetic fields. The average power of EUT is less than 20mW then comply with basic restriction (1999/519/EC) without test.

### 2.2 Table for Filed Antenna

Ant.	Antenna Type	Gain (dBi)
1.	PIFA	2.5



### 3.TEST RESULT

#### 3.1 EMF Exposure Measurement

##### 3.1.1 Limit

##### Basic Restrictions

Council Recommendation 99/519/EC Annex II

Basic restrictions for electric, magnetic and electromagnetic fields (0 Hz to 300 GHz)

Frequency range	Magnetic flux density (mT)	Current density (mA/m <sup>2</sup> ) (rms)	Whole body average SAR (W/kg)	Localized SAR (head and trunk) (W/kg)	Localized SAR (limbs) (W/kg)	Power density, S (W/m <sup>2</sup> )
0Hz	40	-	-	-	-	-
>0-1Hz	-	8	-	-	-	-
1-4Hz	-	8/f	-	-	-	-
4Hz-1000Hz	-	2	-	-	-	-
1000Hz-100kHz	-	f/500	-	-	-	-
100kHz-10MHz	-	f/500	0.08	2	4	-
10MHz-10GHz	-	-	0.08	2	4	-
10GHz-300GHz	-	-	-	-	-	10

Note:

1. f is the frequency in Hz.
2. The basic restriction on the current density is intended to protect against acute exposure effects on central nervous system tissues in the head and trunk of the body and includes a safety factor. The basic restrictions for ELF fields are based on established adverse effects on the central nervous system. Such acute effects are essentially instantaneous and there is no scientific justification to modify the basic restrictions for exposure of short duration. However, since the basic restriction refers to adverse effects on the central nervous system, this basic restriction may permit higher current densities in body tissues other than the central nervous system under the same exposure conditions.
3. Because of electrical inhomogeneity of the body, current densities should be averaged over a cross section of 1 cm<sup>2</sup> perpendicular to the current direction.
4. For frequencies up to 100kHz, peak current density values can be obtained by multiplying the rms value by  $\sqrt{2}$  (=1.414). For pulses of duration tp the equivalent frequency to apply in the basic restrictions should be calculated as  $1/(2tp)$ .

5. For frequencies up to 100kHz and for pulsed magnetic fields, the maximum current density associated with the pulses can be calculated from the rise/fall times and the maximum rate of change of magnetic flux density. The induced current density can then be compared with the appropriate basic restriction.
6. All SAR values are to be averaged over any six-minute period.
7. Localised SAR averaging Mass is any 10g of contiguous tissue; the maximum SAR so obtained should be the value used for the estimation of exposure. These 10g of tissue are intended to be a mass of contiguous tissue with nearly homogeneous electrical properties. In specifying a contiguous mass of tissue, it is recognized that this concept can be used in computational dissymmetry but may present difficulties for direct physical measurements. A simple geometry such as cubic tissue mass can be used provided that the calculated dissymmetric quantities have conservative values relative to the exposure guidelines.
8. For pulses of duration  $t_p$  the equivalent frequency to apply in the basic restrictions should be calculated as  $f = 1/(2t_p)$ . Additionally, for pulsed exposures, in the frequency range 0.3 to 10GHz and for localized exposure of the head, in order to limit and avoid auditory effects caused by thermoplastic expansion, an additional basic restriction is recommended. This is that the SA should not exceed 2mJ kg<sup>-1</sup> averaged over 10g of tissue.

### Reference Levels

Council Recommendation 99/519/EC Annex III Reference levels for electric, magnetic and electromagnetic fields (0Hz to 300GHz)

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (μT)	Equivalent plane wave power density Seq (W/m <sup>2</sup> )
0-1Hz	-	$3,2 \times 10^4$	$4 \times 10^4$	-
1-8Hz	1000	$3,2 \times 10^4 / f^2$	$4 \times 10^4 / f^2$	-
8-25Hz	1000	$4000 / f$	$5000 / f$	-
0.025Hz-0,8kHz	$250 / f$	$4 / f$	$5 / f_{6,25}$	-
0,8-3kHz	$250 / f$	5	6,25	-
3-150kHz	87	5	6,25	-
0,15-1MHz	87	$0.73 / f$	$0.92 / f$	-
1-10MHz	$87 / f^{1/2}$	$0.73 / f$	$0.92 / f$	-
10-400MHz	28	0.073	0.092	2
400-2000MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	$f / 200$
2-300GHz	61	0,16	0,20	10




Note:

1. As indicated in the frequency range column.
  2. For frequencies between 100kHz and 10GHz, Seq, E2, H2 and B2 are to be averaged over any six-minute period.
  3. For frequencies exceeding 10GHz, Seq, E2, H2 and B2 are to be averaged over any 68/1.05-minute period (.in GHz).
  4. No E-field value is provided for frequencies <1Hz, which are effectively static electric fields.
- For most people the annoying perception of surface electric charges will not occur at field strengths less than 20kV/m. Spark discharges causing stress or annoyance should be avoided.

Anbotek

### 3.1.2. Evaluation Routine

#### Low Power Electronic Apparatus for RF exposure evaluation routine



### 3.2 Detailed results

#### 3.2.1 Summary of Results

Frequency (MHz)	Limit (W/ m <sup>2</sup> )	Result (W/ m <sup>2</sup> )	Verdict
GSM900	4.5	1.29	passed
GSM1800	9	0.64	passed

#### 3.2.2 MPE Evaluation

$$S = PG * \text{Duty factor} / 4\pi R^2$$

P = Peak Power Input to antenna (Watts)

G = Antenna Gain (numeric)

R = distance to the center of radiation of antenna (in meter) = 0.20 m

Note:

1) P (Watts) =  $(10^{(\text{dBm} / 10)}) / 1000$

2) G (Antenna gain in numeric) =  $10^{(\text{Antenna gain in dBi} / 10)}$

3) Duty factor = 1

4)  $\pi = 3.142$

The maximum power density at a distance of 0.2 m for EUT is shown as below:

Frequency (MHz)	Antenna Gain(dBi)	Peak Output Power (dBm)	Peak Output Power (W)	Duty factor	Calculated RF Exposure (W/ m <sup>2</sup> )	Limit (W/ m <sup>2</sup> )
GSM900	2.5	31.65	1.46	0.25	1.29	4.5
GSM1800	2.5	28.55	0.72	0.25	0.64	9

#### 3.2.4 Measurement Uncertainty

Extended Uncertainty (k=2) 95% 0.5dB