

RED-Health Test Report

For

Shanghai Wenheng Electronics Technology Co., Ltd.

LoRa Module

Model No.: WH-L101, WH-L100, WH-L102, WH-L103, WH-L104, WH-L105, WH-L106, WH-L107, WH-L108, WH-L109, WH-L200, WH-L201, WH-L202, WH-L203, WH-L204, WH-L205, WH-L206, WH-L207, WH-L208, WH-L209, WH-LR30, WH-LR31, WH-LR32, WH-LR33, WH-LR34, WH-LR35, WH-LR36, WH-LR37, WH-LR38, WH-LR39

Prepared For : Shanghai Wenheng Electronics Technology Co., Ltd.
Address : Room 611, Building5, Xizi International Center No.898 Xiuwen Street, Minhang District, ShangHai

Prepared By : Shenzhen Anbotech Compliance Laboratory Limited
Address : 1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102
Tel: (86) 755-26066440 Fax: (86) 755-26014772

Date of Receipt : Sept. 12, 2018
Report Number : SZAWW180912006-03H
Date of Test : Sept. 13~ Nov. 5, 2018
Date of Report : Nov. 5, 2018

CONTENTS

CONTENTS.....	2
1. GENERAL INFORMATION.....	5
1.1. Client Information.....	5
1.2. Description of Device (EUT).....	5
1.3. Auxiliary Equipment Used During Test.....	5
1.4 Description of Test Facility.....	6
1.5 Measurement Uncertainty.....	6
2. GENERAL PRODUCT INFORMATION.....	7
2.1 Product Function and Intended Use.....	7
2.2 Ratings and System Detail.....	7
3. EN 62479 REQUIREMENT.....	8
3.1 General Description of Applied Standards.....	8
3.2 Human exposure to the Electromagnetic fields.....	8
3.3 RF Exposure Evaluation.....	8

TEST REPORT

Applicant : Shanghai Wenheng Electronics Technology Co., Ltd.
Manufacturer : Shanghai Wenheng Electronics Technology Co., Ltd.
Product Name : LoRa Module
Model No. : WH-L101, WH-L100, WH-L102, WH-L103, WH-L104, WH-L105, WH-L106,
WH-L107, WH-L108, WH-L109, WH-L200, WH-L201, WH-L202, WH-L203,
WH-L204, WH-L205, WH-L206, WH-L207, WH-L208, WH-L209, WH-LR30,
WH-LR31, WH-LR32, WH-LR33, WH-LR34, WH-LR35, WH-LR36, WH-LR37,
WH-LR38, WH-LR39
Trade Mark : N.A.
Rating(s) : Input: DC 1.8V~3.6V, 200mA

Test Standard(s) : EN 62479: 2010

The device described above is tested by Shenzhen Anbotech Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report shows the EUT to be technically compliant with the EN 62479: 2010 requirements. The test results are contained in this report and Shenzhen Anbotech Compliance Laboratory Limited is assumed full responsibility for the accuracy and completeness of these tests.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotech Compliance Laboratory Limited.

Date of Test

Sept. 13~ Nov. 5, 2018

Prepared By





(Engineer / Oliay Yang)

Reviewer


(Supervisor / Snowy Meng)

Approved & Authorized Signer


(Manager / Sally Zhang)

1. General Information

1.1. Client Information

Applicant	:	Shanghai Wenheng Electronics Technology Co., Ltd.
Address	:	Room 611, Building5, Xizi International Center No.898 Xiuwen Street, Minhang District, ShangHai
Manufacturer	:	Shanghai Wenheng Electronics Technology Co., Ltd.
Address	:	Room 611, Building5, Xizi International Center No.898 Xiuwen Street, Minhang District, ShangHai
Factory	:	Shanghai Wenheng Electronics Technology Co., Ltd.
Address	:	Room 611, Building5, Xizi International Center No.898 Xiuwen Street, Minhang District, ShangHai

1.2. Description of Device (EUT)

Product Name	:	LoRa Module					
Model No.	:	WH-L101, WH-L100, WH-L102, WH-L103, WH-L104, WH-L105, WH-L106, WH-L107, WH-L108, WH-L109, WH-L200, WH-L201, WH-L202, WH-L203, WH-L204, WH-L205, WH-L206, WH-L207, WH-L208, WH-L209, WH-LR30, WH-LR31, WH-LR32, WH-LR33, WH-LR34, WH-LR35, WH-LR36, WH-LR37, WH-LR38, WH-LR39 (Note: All samples are the same except the color of model appearance, the label and the name, so we prepare "WH-L101" for test only.)					
Trade Mark	:	N.A.					
Test Power Supply	:	AC 100-240V~50/60Hz for adapter					
Test Sample No.	:	S1, S2					
Product Description	:	Operation Frequency:		863MHz, 864MHz, 865MHz, 866MHz, 867MHz, 868MHz, 869MHz, 870MHz			
	:	Number of Channel:		8 Channels			
	:	Modulation Type:		Lora			
	:	Antenna Type:		Column Antenna（Auxiliary Antenna）			
	:	Antenna Gain(Peak):		1 dBi			
	:	Max. Transmitting Power		10.12 dBm Max.			
Remark: 1) For a more detailed features description, please refer to the manufacturer’s specifications or the User’s Manual.							

1.3. Auxiliary Equipment Used During Test

N/A	:	
-----	---	--

1.4 Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, July 31, 2017.

ISED-Registration No.: 8058A-1

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A-1, June 13, 2016.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.
1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102

1.5 Measurement Uncertainty

Parameter	Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±1,5 dB
Power Spectral Density, conducted	±3 dB
Unwanted Emissions, conducted	±3 dB
All emissions, radiated	±6 dB
Temperature	±1 °C
Humidity	±5 %
DC and low frequency voltages	±3 %
Time	±5 %
Duty Cycle	±5 %

2. GENERAL PRODUCT INFORMATION

2.1 Product Function and Intended Use

The submitted sample is wireless transceiver includes transmitter and receiver.

2.2 Ratings and System Detail

Transmitter		
Operation Frequency	:	863MHz, 864MHz, 865MHz, 866MHz, 867MHz, 868MHz, 869MHz, 870MHz
Power Supply	:	AC 100-240V~50/60Hz for adapter

3. EN 62479 REQUIREMENT

3.1 General Description of Applied Standards

Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz).

3.2 Human exposure to the Electromagnetic fields

This International Standard provides simple conformity assessment methods for low-power electronic and electrical equipment to an exposure limit relevant to electromagnetic fields (EMF). If such equipment cannot be shown to comply with the applicable EMF exposure requirements using the methods included in this standard for EMF assessment, then other standards, including IEC 62311 or other (EMF) product standards, may be used for conformity assessment.

3.3 RF Exposure Evaluation

3.3.1 Limit:

According to EN 62479 clause 4.2 Low-power electronic and electrical equipment is deemed to comply with the provisions of this standard if it can be demonstrated using routes B, C or D that the available antenna power and/or the average total radiated power is less than or equal to the applicable low-power exclusion level P_{max} .
 $P_{max} = 20 \text{ mW}$ (13.1dBm) according to ICNIRP guidelines, since the EUT is General public used.

Remark:

B: The input power level to electrical or electronic components that are capable of radiating electromagnetic energy in the relevant frequency range is so low that the available antenna power and/or the average total radiated power cannot exceed the low-power exclusion level defined in EN 62479 clause 4.2

C: The available antenna power and/or the average total radiated power are limited by product standards for transmitters to levels below the low-power exclusion level defined in EN 62479 clause 4.2

D: Measurements or calculations show that the available antenna power and/or the average total radiated power are below the low-power exclusion level defined in EN 62479 clauses 4.2.

3.3.2 Test result

The EIRP of the EUT which are below the max permitted sending level of 20 mW, and then the EUT is not need to conduct SAR measurement.

More details please refer to SZAWW180912006-04W.

----- End of Report -----