



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM181000884602
Page: 1 of 143

TEST REPORT

Application No.: SZEM1810008846CR
Applicant: Jinan USR IOT Technology Limited
Address of Applicant: Floor 2, Wuzhou Scientific Research Building, No.1100 Shunfeng Street,
Gaoxin District, Jinan, Shandong 250101 China
Manufacturer: Jinan USR IOT Technology Limited
Address of Manufacturer: Floor 2, Wuzhou Scientific Research Building, No.1100 Shunfeng Street,
Gaoxin District, Jinan, Shandong, 250101, China
Factory: Jinan USR IOT Technology Limited
Address of Factory: Floor 2, Wuzhou Scientific Research Building, No.1100 Shunfeng Street,
Gaoxin District, Jinan, Shandong, 250101, China
Equipment Under Test (EUT):
EUT Name: Serial to WIFI Module
Model No.: USR-C216
IC: 20326-USRC216
Standard(s) : RSS-247 Issue 2, February 2017
RSS-Gen Issue 5, April 2018
Date of Receipt: 2018-10-10
Date of Test: 2018-10-16 to 2018-11-28
Date of Issue: 2018-12-11

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu

EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2018-12-11		Original

Authorized for issue by:				
				
		<hr/>		
		Bill Chen /Project Engineer		
				
		<hr/>		
		Eric Fu /Reviewer		



2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	RSS-247 Issue 2, February 2017	N/A	RSS-Gen Section 8.3	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 6.2	RSS-Gen Section 8.8	Pass
99% Bandwidth	RSS-247 Issue 2, February 2017	ANSI C63.10 Section 6.9.3	RSS-Gen Section 6.6	Pass
Minimum 6dB Bandwidth	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 11.8.1	RSS-247 Section 5.2(a)	Pass
Conducted Peak Output Power	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 11.9.1	RSS-247 Section 5.4(d)	Pass
Power Spectrum Density	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 11.10.2	RSS-247 Clause 5.2(b)	Pass
Conducted Band Edges Measurement	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 11.12	RSS-247 Section 5.5	Pass
Conducted Spurious Emissions	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 11.11	RSS-247 Section 5.5	Pass
Radiated Emissions which fall in the restricted bands	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 6.10.5	Section 3.3 & RSS-Gen Section 8.9	Pass
Radiated Spurious Emissions	RSS-247 Issue 2, February 2017	ANSI C63.10 (2013) Section 6.4&6.5&6.6	Section 3.3 & RSS-Gen Section 8.9	Pass



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	6
4.1 DETAILS OF E.U.T.	6
4.2 DESCRIPTION OF SUPPORT UNITS	6
4.3 MEASUREMENT UNCERTAINTY	7
4.4 TEST LOCATION.....	8
4.5 TEST FACILITY.....	8
4.6 DEVIATION FROM STANDARDS.....	8
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	8
5 EQUIPMENT LIST.....	9
6 RADIO SPECTRUM TECHNICAL REQUIREMENT	13
6.1 ANTENNA REQUIREMENT	13
6.1.1 Test Requirement:	13
6.1.2 Conclusion	13
7 RADIO SPECTRUM MATTER TEST RESULTS.....	14
7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ).....	14
7.1.1 E.U.T. Operation	15
7.1.2 Test Setup Diagram.....	15
7.1.3 Measurement Procedure and Data.....	15
7.2 99% BANDWIDTH	18
7.2.1 E.U.T. Operation	18
7.2.2 Test Setup Diagram.....	18
7.2.3 Measurement Procedure and Data.....	18
7.3 MINIMUM 6DB BANDWIDTH.....	19
7.3.1 E.U.T. Operation	19
7.3.2 Test Setup Diagram.....	19
7.3.3 Measurement Procedure and Data.....	19
7.4 CONDUCTED PEAK OUTPUT POWER.....	20
7.4.1 E.U.T. Operation	20
7.4.2 Test Setup Diagram.....	20
7.4.3 Measurement Procedure and Data.....	20
7.5 POWER SPECTRUM DENSITY.....	21
7.5.1 E.U.T. Operation	21
7.5.2 Test Setup Diagram.....	21
7.5.3 Measurement Procedure and Data.....	21
7.6 CONDUCTED BAND EDGES MEASUREMENT.....	22
7.6.1 E.U.T. Operation	23
7.6.2 Test Setup Diagram.....	23
7.6.3 Measurement Procedure and Data.....	23
7.7 CONDUCTED SPURIOUS EMISSIONS.....	24
7.7.1 E.U.T. Operation	25
7.7.2 Test Setup Diagram.....	25



7.7.3	Measurement Procedure and Data.....	25
7.8	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	26
7.8.1	E.U.T. Operation	27
7.8.2	Test Setup Diagram.....	27
7.8.3	Measurement Procedure and Data.....	28
7.9	RADIATED SPURIOUS EMISSIONS	61
7.9.1	E.U.T. Operation	62
7.9.2	Test Setup Diagram.....	62
7.9.3	Measurement Procedure and Data.....	63
8	PHOTOGRAPHS.....	90
8.1	TEST SETUP	90
8.2	EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS).....	90
9	APPENDIX.....	91
9.1	APPENDIX RSS247	91-143



4 General Information

4.1 Details of E.U.T.

Power supply:	Supply by Host Host: Rechargeable Li-ion battery 3.7V 400mAh 1.48Wh(Charge by USB) Module: DC 3.3V
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels:	802.11b/g/n(HT20):11 802.11n(HT40):7
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz
Antenna Type:	PIFA
Channel Spacing:	5MHz
Antenna Gain:	1.3dBi

Channel list for 802.11b/g/n(HT20)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Channel list for 802.11n(HT40)

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
3	2422MHz	5	2432MHz	7	2442MHz	9	2452MHz
4	2427MHz	6	2437MHz	8	2447MHz		

Selected Test Channel for 802.11b/g/n(HT20)

Channel	Frequency
The lowest channel (CH1)	2412MHz
The middle channel (CH6)	2437MHz
The highest channel (CH11)	2462MHz

Selected Test Channel for 802.11n(HT40)

Channel	Frequency
The lowest channel (CH3)	2422MHz
The middle channel (CH6)	2437MHz
The highest channel (CH9)	2452MHz

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
-------------	--------------	-----------	------------

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Micro USB Cable	PHILIPS	SWR2101	REF. No.SEA0700
Adapter	Apple	A1357 W010A051	REF. No.SEA0500
Host	Customer to provide	N/A	N/A

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power	$\pm 0.75\text{dB}$
5	RF power density	$\pm 2.84\text{dB}$
6	Conducted Spurious emissions	$\pm 0.75\text{dB}$
7	RF Radiated power	$\pm 4.5\text{dB}$ (below 1GHz)
		$\pm 4.8\text{dB}$ (above 1GHz)
8	Radiated Spurious emission test	$\pm 4.5\text{dB}$ (Below 1GHz)
		$\pm 4.8\text{dB}$ (Above 1GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Supply voltages	$\pm 1.5\%$
12	Time	$\pm 3\%$



4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2017-05-10	2020-05-09
Measurement Software	AUDIX	e3 V5.4.1221d	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2018-07-12	2019-07-11
LISN	Rohde & Schwarz	ENV216	SEM007-01	2018-09-25	2019-09-24
LISN	ETS-LINDGREN	3816/2	SEM007-02	2018-04-02	2019-04-01
EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2018-04-02	2019-04-01

99% Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2018-09-25	2019-09-24
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2018-09-27	2019-09-26
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2018-07-12	2019-07-11
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2018-09-27	2019-09-26
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2018-09-25	2019-09-24

Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2018-09-25	2019-09-24
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2018-09-27	2019-09-26
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2018-07-12	2019-07-11
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2018-09-27	2019-09-26
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2018-09-25	2019-09-24

Conducted Peak Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2018-09-25	2019-09-24
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2018-09-27	2019-09-26
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2018-07-12	2019-07-11
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2018-09-27	2019-09-26
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2018-09-25	2019-09-24



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM181000884602

Page: 10 of 143

Power Spectrum Density					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2018-09-25	2019-09-24
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2018-09-27	2019-09-26
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2018-07-12	2019-07-11
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2018-09-27	2019-09-26
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2018-09-25	2019-09-24

Conducted Band Edges Measurement					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2018-09-25	2019-09-24
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2018-09-27	2019-09-26
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2018-07-12	2019-07-11
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2018-09-27	2019-09-26
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2018-09-25	2019-09-24

Conducted Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2018-09-25	2019-09-24
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2018-09-27	2019-09-26
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2018-07-12	2019-07-11
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2018-09-27	2019-09-26
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2018-09-25	2019-09-24

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018-03-13	2021-03-12
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2018-07-12	2019-07-11
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2018-04-02	2019-04-01
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017-06-27	2020-06-26



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM181000884602

Page: 11 of 143

Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2018-04-13	2021-04-12
Horn Antenna (15GHz-40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2018-09-25	2019-09-24
Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2018-09-27	2019-09-26
Pre-amplifier (18-26GHz)	Rohde & Schwarz	CH14-H052	SEM005-17	2018-04-02	2019-04-01
Pre-amplifier (26GHz-40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2018-04-02	2019-04-01
DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2018-09-25	2019-09-24
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21
Band filter	N/A	N/A	SEM023-01	N/A	N/A

Radiated Spurious Emissions

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018-03-13	2021-03-12
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2018-07-12	2019-07-11
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2018-04-02	2019-04-01
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017-06-27	2020-06-26
Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2018-04-13	2021-04-12
Horn Antenna (15GHz-40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2018-09-25	2019-09-24
Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2018-09-27	2019-09-26
Pre-amplifier(18-26GHz)	Rohde & Schwarz	CH14-H052	SEM005-17	2018-04-02	2019-04-01
Pre-amplifier (26GHz-40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2018-04-02	2019-04-01
DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2018-09-25	2019-09-24
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21
Band filter	N/A	N/A	SEM023-01	N/A	N/A



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM181000884602

Page: 12 of 143

RE in Chamber					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2017-08-05	2020-08-04
MXE EMI Receiver (20Hz-8.4GHz)	Agilent Technologies	N9038A	SEM004-05	2018-09-25	2019-09-24
BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEM003-01	2017-06-27	2020-06-26
Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEM005-01	2018-04-02	2019-04-01
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2018-07-12	2019-07-11

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2018-09-27	2019-09-26
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2018-09-27	2019-09-26
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2018-09-27	2019-09-26
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2018-04-08	2019-04-07



6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

RSS-Gen Section 8.3

6.1.2 Conclusion

Standard Requirement:

Testing shall be performed using the highest gain antenna of each combination of licence-exempt transmitter and antenna type, with the transmitter output power set at the maximum level. When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 1.3dBi.

Antenna location: Refer to Appendix(Internal photos)



7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement RSS-Gen Section 8.8
Test Method: ANSI C63.10 (2013) Section 6.2
Limit:

Frequency of emission(MHz)	Conducted limit(dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		


7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23 °C Humidity: 63.7 % RH Atmospheric Pressure: 1010 mbar

Test mode a: Charge+TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.1.2 Test Setup Diagram




7.1.3 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor

Mode:a; Line:Live Line



Site : Shielding Room


Condition: Line

Job No. : 08846CR

Test mode: a

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.17	0.01	9.66	25.78	35.45	55.16	-19.71	Peak
2	0.41	0.05	9.67	30.75	40.47	47.59	-7.12	Peak
3	0.88	0.08	9.74	27.78	37.60	46.00	-8.40	Peak
4	1.79	0.15	9.72	23.72	33.59	46.00	-12.41	Peak
5	4.29	0.16	9.73	28.17	38.06	46.00	-7.94	Peak
6	6.09	0.17	9.76	27.76	37.69	50.00	-12.31	Peak

Mode:a; Line:Neutral Line



Site : Shielding Room

Condition: Neutral

Job No. : 08846CR

Test mode: a

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.17	0.02	9.64	21.58	31.24	54.94	-23.70	Peak
2	0.44	0.05	9.65	28.13	37.83	47.15	-9.32	Peak
3	0.69	0.07	9.65	23.68	33.40	46.00	-12.60	Peak
4	1.66	0.14	9.70	21.28	31.12	46.00	-14.88	Peak
5	3.66	0.16	9.69	24.47	34.32	46.00	-11.68	Peak
6	14.21	0.20	10.31	28.73	39.24	50.00	-10.76	Peak

7.2 99% Bandwidth

Test Requirement RSS-Gen Section 6.6

Test Method: ANSI C63.10 Section 6.9.3


7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 24.3 °C Humidity: 42.6 % RH Atmospheric Pressure: 1010 mbar

Test mode b:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.2.2 Test Setup Diagram



7.2.3 Measurement Procedure and Data

The detailed test data see: Appendix RSS247

7.3 Minimum 6dB Bandwidth

Test Requirement	RSS-247 Section 5.2(a)
Test Method:	ANSI C63.10 (2013) Section 11.8.1
Limit:	≥ 500 kHz


7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 24.3 °C Humidity: 42.6 % RH Atmospheric Pressure: 1010 mbar

Test mode b:TX mode Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.3.2 Test Setup Diagram



7.3.3 Measurement Procedure and Data

The detailed test data see: Appendix RSS247

7.4 Conducted Peak Output Power

Test Requirement RSS-247 Section 5.4(d)
 Test Method: ANSI C63.10 (2013) Section 11.9.1
 Limit:


7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 24.3 °C Humidity: 42.6 % RH Atmospheric Pressure: 1010 mbar

Test mode b:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.4.2 Test Setup Diagram



7.4.3 Measurement Procedure and Data

The detailed test data see: Appendix RSS247

7.5 Power Spectrum Density

Test Requirement RSS-247 Clause 5.2(b)
 Test Method: ANSI C63.10 (2013) Section 11.10.2
 Limit: $\leq 8\text{dBm}$ in any 3 kHz band during any time interval of continuous transmission


7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 24.3 °C Humidity: 42.6 % RH Atmospheric Pressure: 1010 mbar

Test mode b:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.5.2 Test Setup Diagram



7.5.3 Measurement Procedure and Data

The detailed test data see: Appendix RSS247



7.6 Conducted Band Edges Measurement

Test Requirement RSS-247 Section 5.5

Test Method: ANSI C63.10 (2013) Section 11.12

Limit: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.


7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 24.3 °C Humidity: 42.6 % RH Atmospheric Pressure: 1010 mbar

Test mode b:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.6.2 Test Setup Diagram



7.6.3 Measurement Procedure and Data

The detailed test data see: Appendix RSS247



7.7 Conducted Spurious Emissions

Test Requirement RSS-247 Section 5.5

Test Method: ANSI C63.10 (2013) Section 11.11

Limit: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.


7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 24.3 °C Humidity: 42.6 % RH Atmospheric Pressure: 1010 mbar

Test mode b:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.7.2 Test Setup Diagram



7.7.3 Measurement Procedure and Data

The detailed test data see: Appendix RSS247



7.8 Radiated Emissions which fall in the restricted bands

Test Requirement Section 3.3 & RSS-Gen Section 8.9

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 21.8 °C Humidity: 63.4 % RH Atmospheric Pressure: 1010 mbar

Pretest these
mode to find the
worst case:


a: Charge+TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

b: TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

The worst case
for final test:

a: Charge+TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.8.2 Test Setup Diagram



7.8.3 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamp Factor}$

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Mode:a; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:Low




Site : chamber
Condition : 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2412 Band edge
Note : 2.4G WiFi 11B
Power Setting: 31

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2364.087	5.44	28.47	41.16	47.84	40.59	74.00	-33.41	peak
2	2390.000	5.47	28.52	41.17	45.86	38.68	74.00	-35.32	peak
3 *	2412.000	5.50	28.56	41.18	90.22	83.10	74.00	9.10	peak



Mode:a; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:Low




Site : chamber
Condition : 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2412 Band edge
Note : 2.4G WiFi 11B
Power Setting: 31

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.395	5.47	28.52	41.17	37.42	30.24	54.00	-23.76	Average
2	2390.000	5.47	28.52	41.17	37.11	29.93	54.00	-24.07	Average
3 *	2412.000	5.50	28.56	41.18	86.82	79.70	54.00	25.70	Average



Mode:a; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:Low




Site : chamber
Condition : 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2412 Band edge
Note : 2.4G WiFi 11B
Power Setting: 31

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2359.541	5.43	28.47	41.16	48.05	40.79	74.00	-33.21	Peak
2	2390.000	5.47	28.52	41.17	45.66	38.48	74.00	-35.52	Peak
3 *	2412.000	5.50	28.56	41.18	88.31	81.19	74.00	7.19	Peak



Mode:a; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:Low




Site : chamber
Condition : 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2412 Band edge
Note : 2.4G WiFi 11B
Power Setting: 31

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2385.615	5.47	28.51	41.17	37.12	29.93	54.00	-24.07	Average
2	2390.000	5.47	28.52	41.17	36.89	29.71	54.00	-24.29	Average
3 *	2412.000	5.50	28.56	41.18	84.64	77.52	54.00	23.52	Average



Mode:a; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:High




Site : chamber
Condition : 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2462 Band edge
Note : 2.4G WiFi 11B
Power Setting: 35

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	5.57	28.64	41.20	92.57	85.58	74.00	11.58 peak
2	2483.500	5.60	28.67	41.21	46.20	39.26	74.00	-34.74 peak
3	2493.795	5.61	28.69	41.21	48.84	41.93	74.00	-32.07 peak



Mode:a; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:High




Site : chamber
Condition : 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2462 Band edge
Note : 2.4G WiFi 11B
Power Setting: 35

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	5.57	28.64	41.20	89.82	82.83	54.00	28.83 Average
2	2483.500	5.60	28.67	41.21	37.44	30.50	54.00	-23.50 Average
3	2499.748	5.62	28.70	41.22	37.67	30.77	54.00	-23.23 Average



Mode:a; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:High




Site : chamber
Condition : 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2462 Band edge
Note : 2.4G WiFi 11B
Power Setting: 35

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	5.57	28.64	41.20	93.22	86.23	74.00	12.23 Peak
2	2483.500	5.60	28.67	41.21	46.55	39.61	74.00	-34.39 Peak
3	2497.476	5.62	28.70	41.22	48.70	41.80	74.00	-32.20 Peak



Mode:a; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:High




Site : chamber
Condition : 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2462 Band edge
Note : 2.4G WiFi 11B
Power Setting: 35

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	5.57	28.64	41.20	90.33	83.34	54.00	29.34 Average
2	2483.500	5.60	28.67	41.21	37.42	30.48	54.00	-23.52 Average
3	2499.848	5.62	28.70	41.22	37.70	30.80	54.00	-23.20 Average



Mode:a; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:Low




Site : chamber
Condition : 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2412 Band edge
Note : 2.4G WiFi 11G
Power Setting: 36

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.847	5.47	28.52	41.17	67.34	60.16	74.00	-13.84	peak
2	2390.000	5.47	28.52	41.17	66.14	58.96	74.00	-15.04	peak
3 *	2412.000	5.50	28.56	41.18	103.80	96.68	74.00	22.68	peak



Mode:a; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:Low




Site : chamber
Condition : 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2412 Band edge
Note : 2.4G WiFi 11G
Power Setting: 36

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	5.47	28.52	41.17	56.40	49.22	54.00	-4.78	Average
2	2390.000	5.47	28.52	41.17	56.40	49.22	54.00	-4.78	Average
3 *	2412.000	5.50	28.56	41.18	96.75	89.63	54.00	35.63	Average



Mode:a; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:Low




Site : chamber
Condition : 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2412 Band edge
Note : 2.4G WiFi 11G
Power Setting: 36

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	5.47	28.52	41.17	67.65	60.47	74.00	-13.53	Peak
2	2390.000	5.47	28.52	41.17	67.65	60.47	74.00	-13.53	Peak
3 *	2412.000	5.50	28.56	41.18	105.88	98.76	74.00	24.76	Peak



Mode:a; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:Low




Site : chamber
Condition : 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2412 Band edge
Note : 2.4G WiFi 11G
Power Setting: 36

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.726	5.47	28.52	41.17	56.31	49.13	54.00	-4.87	Average
2	2390.000	5.47	28.52	41.17	56.08	48.90	54.00	-5.10	Average
3 *	2412.000	5.50	28.56	41.18	98.49	91.37	54.00	37.37	Average



Mode:a; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:High




Site : chamber
Condition : 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2462 Band edge
Note : 2.4G WiFi 11G
Power Setting: 36

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	5.57	28.64	41.20	104.01	97.02	74.00	23.02 peak
2	2483.500	5.60	28.67	41.21	69.87	62.93	74.00	-11.07 peak
3	2483.890	5.60	28.67	41.21	71.54	64.60	74.00	-9.40 peak



Mode:a; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:High




Site : chamber
Condition : 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2462 Band edge
Note : 2.4G WiFi 11G
Power Setting: 36

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	5.57	28.64	41.20	96.51	89.52	54.00	35.52 Average
2	2483.500	5.60	28.67	41.21	57.31	50.37	54.00	-3.63 Average
3	2483.840	5.60	28.67	41.21	56.91	49.97	54.00	-4.03 Average



Mode:a; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:High




Site : chamber
Condition : 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2462 Band edge
Note : 2.4G WiFi 11G
Power Setting: 36

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	5.57	28.64	41.20	105.18	98.19	74.00	24.19 Peak
2	2483.500	5.60	28.67	41.21	70.91	63.97	74.00	-10.03 Peak
3	2485.496	5.60	28.68	41.21	71.77	64.84	74.00	-9.16 Peak



Mode:a; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:High




Site : chamber
Condition : 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2462 Band edge
Note : 2.4G WiFi 11G
Power Setting: 36

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 *	2462.000	5.57	28.64	41.20	97.90	90.91	54.00	36.91	Average
2	2483.500	5.60	28.67	41.21	57.90	50.96	54.00	-3.04	Average
3	2483.790	5.60	28.67	41.21	57.55	50.61	54.00	-3.39	Average



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:Low




Site : chamber
Condition : 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2412 Band edge
Note : 2.4G WiFi 11N 20
Power Setting: 34

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.605	5.47	28.52	41.17	68.41	61.23	74.00	-12.77	peak
2	2390.000	5.47	28.52	41.17	67.81	60.63	74.00	-13.37	peak
3 *	2412.000	5.50	28.56	41.18	101.24	94.12	74.00	20.12	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:Low




Site : chamber
Condition : 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2412 Band edge
Note : 2.4G WiFi 11N 20
Power Setting: 34

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	5.47	28.52	41.17	52.90	45.72	54.00	-8.28	Average
2	2390.000	5.47	28.52	41.17	52.90	45.72	54.00	-8.28	Average
3 *	2412.000	5.50	28.56	41.18	94.03	86.91	54.00	32.91	Average



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:Low




Site : chamber
Condition : 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2412 Band edge
Note : 2.4G WiFi 11N 20
Power Setting: 34

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	5.47	28.52	41.17	69.88	62.70	74.00	-11.30	Peak
2	2390.000	5.47	28.52	41.17	69.88	62.70	74.00	-11.30	Peak
3 *	2412.000	5.50	28.56	41.18	104.49	97.37	74.00	23.37	Peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:Low




Site : chamber
Condition : 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2412 Band edge
Note : 2.4G WiFi 11N 20
Power Setting: 34

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	5.47	28.52	41.17	53.69	46.51	54.00	-7.49	Average
2	2390.000	5.47	28.52	41.17	53.69	46.51	54.00	-7.49	Average
3 *	2412.000	5.50	28.56	41.18	96.55	89.43	54.00	35.43	Average



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:High




Site : chamber
Condition : 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2462 Band edge
Note : 2.4G WiFi 11N 20
Power Setting: 32

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	5.57	28.64	41.20	102.71	95.72	74.00	21.72 peak
2	2483.500	5.60	28.67	41.21	70.48	63.54	74.00	-10.46 peak
3	2483.790	5.60	28.67	41.21	70.14	63.20	74.00	-10.80 peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:High




Site : chamber
Condition : 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2462 Band edge
Note : 2.4G WiFi 11N 20
Power Setting: 32

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	5.57	28.64	41.20	94.46	87.47	54.00	33.47 Average
2	2483.500	5.60	28.67	41.21	54.79	47.85	54.00	-6.15 Average
3	2483.940	5.60	28.67	41.21	54.74	47.80	54.00	-6.20 Average



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:High




Site : chamber
Condition : 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2462 Band edge
Note : 2.4G WiFi 11N 20
Power Setting: 32

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	5.57	28.64	41.20	103.76	96.77	74.00	22.77 Peak
2	2483.500	5.60	28.67	41.21	71.94	65.00	74.00	-9.00 Peak
3	2483.790	5.60	28.67	41.21	71.44	64.50	74.00	-9.50 Peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:High




Site : chamber
Condition : 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2462 Band edge
Note : 2.4G WiFi 11N 20
Power Setting: 32

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2462.000	5.57	28.64	41.20	96.21	89.22	54.00	35.22 Average
2	2483.500	5.60	28.67	41.21	56.41	49.47	54.00	-4.53 Average
3	2483.990	5.60	28.67	41.21	56.36	49.42	54.00	-4.58 Average



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:40MHz; Channel:Low




Site : chamber
Condition : 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2422 Band edge
Note : 2.4G WiFi 11N 40
Power Setting: 35

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.174	5.47	28.52	41.17	68.93	61.75	74.00	-12.25	peak
2	2390.000	5.47	28.52	41.17	66.89	59.71	74.00	-14.29	peak
3 *	2422.000	5.52	28.57	41.19	99.45	92.35	74.00	18.35	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:40MHz; Channel:Low




Site : chamber
Condition : 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2422 Band edge
Note : 2.4G WiFi 11N 40
Power Setting: 35

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.827	5.47	28.52	41.17	55.60	48.42	54.00	-5.58	Average
2	2390.000	5.47	28.52	41.17	55.52	48.34	54.00	-5.66	Average
3 *	2422.000	5.52	28.57	41.19	92.40	85.30	54.00	31.30	Average



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:40MHz; Channel:Low




Site : chamber
Condition : 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2422 Band edge
Note : 2.4G WiFi 11N 40
Power Setting: 35

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2385.771	5.47	28.51	41.17	69.88	62.69	74.00	-11.31	Peak
2	2390.000	5.47	28.52	41.17	68.77	61.59	74.00	-12.41	Peak
3 *	2422.000	5.52	28.57	41.19	101.53	94.43	74.00	20.43	Peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:40MHz; Channel:Low




Site : chamber
Condition : 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2422 Band edge
Note : 2.4G WiFi 11N 40
Power Setting: 35

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.625	5.47	28.52	41.17	56.81	49.63	54.00	-4.37	Average
2	2390.000	5.47	28.52	41.17	56.59	49.41	54.00	-4.59	Average
3 *	2422.000	5.52	28.57	41.19	94.19	87.09	54.00	33.09	Average



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:40MHz; Channel:High




Site : chamber
Condition : 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2452 Band edge
Note : 2.4G WiFi 11N 40
Power Setting: 32

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2452.000	5.56	28.62	41.20	98.86	91.84	74.00	17.84 peak
2	2483.500	5.60	28.67	41.21	66.76	59.82	74.00	-14.18 peak
3	2484.570	5.60	28.68	41.21	67.61	60.68	74.00	-13.32 peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:40MHz; Channel:High




Site : chamber
Condition : 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2452 Band edge
Note : 2.4G WiFi 11N 40
Power Setting: 32

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2452.000	5.56	28.62	41.20	91.16	84.14	54.00	30.14 Average
2	2483.500	5.60	28.67	41.21	53.55	46.61	54.00	-7.39 Average
3	2484.711	5.60	28.68	41.21	54.28	47.35	54.00	-6.65 Average



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:40MHz; Channel:High




Site : chamber
Condition : 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2452 Band edge
Note : 2.4G WiFi 11N 40
Power Setting: 32

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2452.000	5.56	28.62	41.20	100.78	93.76	74.00	19.76 Peak
2	2483.500	5.60	28.67	41.21	67.15	60.21	74.00	-13.79 Peak
3	2484.711	5.60	28.68	41.21	69.50	62.57	74.00	-11.43 Peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:40MHz; Channel:High



Site : chamber
Condition : 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2452 Band edge
Note : 2.4G WiFi 11N 40
Power Setting: 32

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 *	2452.000	5.56	28.62	41.20	93.08	86.06	54.00	32.06 Average
2	2483.500	5.60	28.67	41.21	55.68	48.74	54.00	-5.26 Average
3	2484.147	5.60	28.67	41.21	56.41	49.47	54.00	-4.53 Average



7.9 Radiated Spurious Emissions

Test Requirement Section 3.3 & RSS-Gen Section 8.9

Test Method: ANSI C63.10 (2013) Section 6.4&6.5&6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 23.6 °C Humidity: 62.4 % RH Atmospheric Pressure: 1010 mbar

Pretest these
mode to find the
worst case:


a: Charge+TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

b: TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

The worst case
for final test:

a: Charge+TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

7.9.2 Test Setup Diagram



7.9.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Preamplifier Factor}$$
- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



30MHz~1GHz

Mode: a; Polarization: Horizontal




Condition: 3m HORIZONTAL

Job No. : 08846CR

Test mode: a

	Freq	Cable	Ant	Preamp	Read		Limit	Over
	MHz	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	31.29	0.60	21.77	27.66	24.03	18.74	40.00	-21.26
2	177.51	1.37	15.85	27.53	34.23	23.92	43.50	-19.58
3	211.53	1.47	16.91	27.53	34.79	25.64	43.50	-17.86
4	251.18	1.68	18.97	27.54	30.27	23.38	46.00	-22.62
5	845.09	3.39	29.11	27.26	24.86	30.10	46.00	-15.90
6 pp	932.27	3.63	29.97	26.97	23.98	30.61	46.00	-15.39

Mode: a; Polarization: Vertical



Condition: 3m VERTICAL

Job No. : 08846CR


Test mode: a

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	68.87	0.80	12.84	27.53	35.52	21.63	40.00	-18.37
2	121.98	1.26	13.16	27.52	39.85	26.75	43.50	-16.75
3	129.92	1.28	13.41	27.52	40.16	27.33	43.50	-16.17
4	174.42	1.36	15.79	27.53	35.76	25.38	43.50	-18.12
5	177.51	1.37	15.85	27.53	35.95	25.64	43.50	-17.86
6 pp	818.83	3.28	28.76	27.35	25.58	30.27	46.00	-15.73



Above 1GHz


Mode:a; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2412 TX RSE
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1658.337	5.28	26.50	41.51	46.19	36.46	74.00	-37.54	peak
2	4392.376	7.44	33.42	42.40	46.95	45.41	74.00	-28.59	peak
3	4824.000	7.91	34.00	42.47	46.55	45.99	74.00	-28.01	peak
4	6488.754	11.52	35.59	41.22	44.74	50.63	74.00	-23.37	peak
5	7236.000	10.07	36.09	40.69	42.58	48.05	74.00	-25.95	peak
6	9648.000	10.77	37.69	37.68	40.12	50.90	74.00	-23.10	peak

Mode:a; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2412 TX RSE
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1538.281	5.43	25.98	41.43	45.67	35.65	74.00	-38.35	peak
2	4367.058	7.41	33.37	42.39	46.46	44.85	74.00	-29.15	peak
3	4824.000	7.91	34.00	42.47	47.19	46.63	74.00	-27.37	peak
4	6602.265	11.24	35.66	41.14	45.82	51.58	74.00	-22.42	peak
5	7236.000	10.07	36.09	40.69	43.15	48.62	74.00	-25.38	peak
6	9648.000	10.77	37.69	37.68	38.95	49.73	74.00	-24.27	peak



Mode:a; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2437 TX RSE
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1556.169	5.41	26.06	41.44	45.60	35.63	74.00	-38.37	peak
2	4341.886	7.38	33.33	42.39	46.32	44.64	74.00	-29.36	peak
3	4874.000	7.96	34.05	42.48	47.64	47.17	74.00	-26.83	peak
4	6488.754	11.52	35.59	41.22	44.78	50.67	74.00	-23.33	peak
5	7311.000	10.05	36.15	40.64	43.98	49.54	74.00	-24.46	peak
6	9748.000	10.82	37.75	37.54	38.79	49.82	74.00	-24.18	peak




Mode:a; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:middle



Site : chamber
Condition: 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2437 TX RSE
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1542.733	5.42	26.00	41.43	47.18	37.17	74.00	-36.83	peak
2	4379.699	7.43	33.39	42.40	46.70	45.12	74.00	-28.88	peak
3	4874.000	7.96	34.05	42.48	47.93	47.46	74.00	-26.54	peak
4	6303.890	11.17	35.41	41.37	45.43	50.64	74.00	-23.36	peak
5	7311.000	10.05	36.15	40.64	43.88	49.44	74.00	-24.56	peak
6	9748.000	10.82	37.75	37.54	39.43	50.46	74.00	-23.54	peak

Mode:a; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2462 TX RSE
Note : 2.4G WIFI 11B

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5.31	26.38	41.49	46.95	37.15	74.00	-36.85	peak
2	7.47	33.46	42.40	46.03	44.56	74.00	-29.44	peak
3	8.01	34.11	42.49	47.21	46.84	74.00	-27.16	peak
4	11.52	35.59	41.22	45.59	51.48	74.00	-22.52	peak
5	10.03	36.21	40.59	42.18	47.83	74.00	-26.17	peak
6	10.87	37.81	37.41	39.26	50.53	74.00	-23.47	peak



Mode:a; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2462 TX RSE
Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1583.392	5.37	26.18	41.46	45.34	35.43	74.00	-38.57	peak
2	4469.214	7.53	33.55	42.41	46.21	44.88	74.00	-29.12	peak
3	4924.000	8.01	34.11	42.49	47.05	46.68	74.00	-27.32	peak
4	6564.209	11.35	35.64	41.17	45.28	51.10	74.00	-22.90	peak
5	7386.000	10.03	36.21	40.59	42.98	48.63	74.00	-25.37	peak
6	9848.000	10.87	37.81	37.41	38.24	49.51	74.00	-24.49	peak



Mode:a; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2412 TX RSE
Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1503.119	5.48	25.81	41.41	45.27	35.15	74.00	-38.85	peak
2	4291.977	7.33	33.24	42.38	47.02	45.21	74.00	-28.79	peak
3	4824.000	7.91	34.00	42.47	47.62	47.06	74.00	-26.94	peak
4	6231.427	11.03	35.34	41.42	45.83	50.78	74.00	-23.22	peak
5	7236.000	10.07	36.09	40.69	44.30	49.77	74.00	-24.23	peak
6	9648.000	10.77	37.69	37.68	38.43	49.21	74.00	-24.79	peak



Mode:a; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2412 TX RSE
Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1634.543	5.31	26.40	41.49	45.98	36.20	74.00	-37.80	peak
2	4367.058	7.41	33.37	42.39	46.87	45.26	74.00	-28.74	peak
3	4824.000	7.91	34.00	42.47	46.15	45.59	74.00	-28.41	peak
4	6815.551	10.64	35.79	40.98	45.35	50.80	74.00	-23.20	peak
5	7236.000	10.07	36.09	40.69	43.58	49.05	74.00	-24.95	peak
6	9648.000	10.77	37.69	37.68	40.15	50.93	74.00	-23.07	peak



Mode:a; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2437 TX RSE
Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1702.042	5.23	26.68	41.53	44.76	35.14	74.00	-38.86	peak
2	4405.090	7.46	33.44	42.40	46.75	45.25	74.00	-28.75	peak
3	4874.000	7.96	34.05	42.48	47.23	46.76	74.00	-27.24	peak
4	6414.167	11.38	35.52	41.28	44.22	49.84	74.00	-24.16	peak
5	7311.000	10.05	36.15	40.64	43.52	49.08	74.00	-24.92	peak
6	9748.000	10.82	37.75	37.54	39.42	50.45	74.00	-23.55	peak



Mode:a; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2437 TX RSE
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1516.210	5.46	25.87	41.42	46.35	36.26	74.00	-37.74	peak
2	4062.629	7.06	32.82	42.34	48.30	45.84	74.00	-28.16	peak
3	4874.000	7.96	34.05	42.48	46.24	45.77	74.00	-28.23	peak
4	6795.879	10.69	35.78	41.00	44.03	49.50	74.00	-24.50	peak
5	7311.000	10.05	36.15	40.64	45.18	50.74	74.00	-23.26	peak
6	9748.000	10.82	37.75	37.54	39.33	50.36	74.00	-23.64	peak



Mode:a; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2462 TX RSE
Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1663.137	5.27	26.52	41.51	45.86	36.14	74.00	-37.86	peak
2	4405.090	7.46	33.44	42.40	47.23	45.73	74.00	-28.27	peak
3	4924.000	8.01	34.11	42.49	46.50	46.13	74.00	-27.87	peak
4	6507.536	11.52	35.60	41.21	45.17	51.08	74.00	-22.92	peak
5	7386.000	10.03	36.21	40.59	42.81	48.46	74.00	-25.54	peak
6	9848.000	10.87	37.81	37.41	38.80	50.07	74.00	-23.93	peak



Mode:a; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2462 TX RSE
Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1639.274	5.30	26.42	41.49	45.35	35.58	74.00	-38.42	peak
2	4279.589	7.31	33.22	42.38	46.82	44.97	74.00	-29.03	peak
3	4924.000	8.01	34.11	42.49	47.50	47.13	74.00	-26.87	peak
4	6583.209	11.30	35.65	41.15	44.73	50.53	74.00	-23.47	peak
5	7386.000	10.03	36.21	40.59	42.35	48.00	74.00	-26.00	peak
6	9848.000	10.87	37.81	37.41	39.28	50.55	74.00	-23.45	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2412 TX RSE
Note : 2.4G WIFI 11N 20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1542.733	5.42	26.00	41.43	45.72	35.71	74.00	-38.29	peak
2	4456.315	7.51	33.53	42.41	46.72	45.35	74.00	-28.65	peak
3	4824.000	7.91	34.00	42.47	47.74	47.18	74.00	-26.82	peak
4	6432.732	11.41	35.54	41.27	45.49	51.17	74.00	-22.83	peak
5	7236.000	10.07	36.09	40.69	42.83	48.30	74.00	-25.70	peak
6	9648.000	10.77	37.69	37.68	38.87	49.65	74.00	-24.35	peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2412 TX RSE
Note : 2.4G WIFI 11N 20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1578.822	5.38	26.16	41.46	45.29	35.37	74.00	-38.63	peak
2	4405.090	7.46	33.44	42.40	46.77	45.27	74.00	-28.73	peak
3	4824.000	7.91	34.00	42.47	46.66	46.10	74.00	-27.90	peak
4	6377.195	11.31	35.48	41.31	45.74	51.22	74.00	-22.78	peak
5	7236.000	10.07	36.09	40.69	42.29	47.76	74.00	-26.24	peak
6	9648.000	10.77	37.69	37.68	39.64	50.42	74.00	-23.58	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2437 TX RSE
Note : 2.4G WIFI 11N 20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1529.414	5.44	25.94	41.43	46.58	36.53	74.00	-37.47	peak
2	4456.315	7.51	33.53	42.41	46.88	45.51	74.00	-28.49	peak
3	4874.000	7.96	34.05	42.48	46.29	45.82	74.00	-28.18	peak
4	6995.172	10.14	35.90	40.86	45.01	50.19	74.00	-23.81	peak
5	7311.000	10.05	36.15	40.64	43.12	48.68	74.00	-25.32	peak
6	9748.000	10.82	37.75	37.54	39.05	50.08	74.00	-23.92	peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2437 TX RSE
Note : 2.4G WIFI 11N 20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1606.441	5.34	26.28	41.47	45.35	35.50	74.00	-38.50 peak
2	4291.977	7.33	33.24	42.38	46.96	45.15	74.00	-28.85 peak
3	4874.000	7.96	34.05	42.48	46.17	45.70	74.00	-28.30 peak
4	6545.263	11.41	35.63	41.18	44.75	50.61	74.00	-23.39 peak
5	7311.000	10.05	36.15	40.64	44.26	49.82	74.00	-24.18 peak
6	9748.000	10.82	37.75	37.54	39.36	50.39	74.00	-23.61 peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2462 TX RSE
Note : 2.4G WIFI 11N 20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1538.281	5.43	25.98	41.43	45.97	35.95	74.00	-38.05	peak
2	4469.214	7.53	33.55	42.41	46.32	44.99	74.00	-29.01	peak
3	4924.000	8.01	34.11	42.49	47.90	47.53	74.00	-26.47	peak
4	6177.627	10.92	35.28	41.47	46.02	50.75	74.00	-23.25	peak
5	7386.000	10.03	36.21	40.59	41.80	47.45	74.00	-26.55	peak
6	9848.000	10.87	37.81	37.41	39.06	50.33	74.00	-23.67	peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2462 TX RSE
Note : 2.4G WIFI 11N 20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1634.543	5.31	26.40	41.49	46.58	36.80	74.00	-37.20	peak
2	4430.628	7.48	33.48	42.41	46.70	45.25	74.00	-28.75	peak
3	4924.000	8.01	34.11	42.49	48.36	47.99	74.00	-26.01	peak
4	6621.375	11.19	35.67	41.13	45.29	51.02	74.00	-22.98	peak
5	7386.000	10.03	36.21	40.59	42.85	48.50	74.00	-25.50	peak
6	9848.000	10.87	37.81	37.41	39.21	50.48	74.00	-23.52	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2422 TX RSE
Note : 2.4G WIFI 11N 40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1611.091	5.34	26.30	41.48	46.04	36.20	74.00	-37.80	peak
2	4469.214	7.53	33.55	42.41	46.60	45.27	74.00	-28.73	peak
3	4844.000	7.93	34.02	42.48	47.00	46.47	74.00	-27.53	peak
4	6470.026	11.48	35.57	41.24	44.39	50.20	74.00	-23.80	peak
5	7266.000	10.06	36.12	40.67	43.99	49.50	74.00	-24.50	peak
6	9688.000	10.79	37.71	37.63	38.61	49.48	74.00	-24.52	peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2422 TX RSE
Note : 2.4G WIFI 11N 40

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1542.733	5.42	26.00	41.43	46.26	36.25	74.00	-37.75	peak
2	4469.214	7.53	33.55	42.41	46.92	45.59	74.00	-28.41	peak
3	4844.000	7.93	34.02	42.48	46.23	45.70	74.00	-28.30	peak
4	6621.375	11.19	35.67	41.13	44.13	49.86	74.00	-24.14	peak
5	7266.000	10.06	36.12	40.67	44.24	49.75	74.00	-24.25	peak
6	9688.000	10.79	37.71	37.63	38.46	49.33	74.00	-24.67	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:40MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2437 TX RSE
Note : 2.4G WIFI 11N 40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1672.779	5.26	26.56	41.52	44.84	35.14	74.00	-38.86	peak
2	4443.453	7.50	33.50	42.41	47.13	45.72	74.00	-28.28	peak
3	4874.000	7.96	34.05	42.48	46.76	46.29	74.00	-27.71	peak
4	6526.373	11.46	35.62	41.20	43.78	49.66	74.00	-24.34	peak
5	7311.000	10.05	36.15	40.64	44.58	50.14	74.00	-23.86	peak
6	9748.000	10.82	37.75	37.54	40.00	51.03	74.00	-22.97	peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:40MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2437 TX RSE
Note : 2.4G WIFI 11N 40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1611.091	5.34	26.30	41.48	46.12	36.28	74.00	-37.72	peak
2	4430.628	7.48	33.48	42.41	47.35	45.90	74.00	-28.10	peak
3	4874.000	7.96	34.05	42.48	46.80	46.33	74.00	-27.67	peak
4	6322.136	11.20	35.43	41.35	46.12	51.40	74.00	-22.60	peak
5	7311.000	10.05	36.15	40.64	45.21	50.77	74.00	-23.23	peak
6	9748.000	10.82	37.75	37.54	37.77	48.80	74.00	-25.20	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 08845CR/08846CR
Mode : 2452 TX RSE
Note : 2.4G WIFI 11N 40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1667.951	5.27	26.54	41.51	45.40	35.70	74.00	-38.30	peak
2	4193.872	7.21	33.06	42.36	48.43	46.34	74.00	-27.66	peak
3	4904.000	7.99	34.09	42.48	46.29	45.89	74.00	-28.11	peak
4	6698.373	10.97	35.72	41.07	45.40	51.02	74.00	-22.98	peak
5	7356.000	10.04	36.19	40.61	42.40	48.02	74.00	-25.98	peak
6	9808.000	10.85	37.79	37.46	38.83	50.01	74.00	-23.99	peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 08845CR/08846CR
Mode : 2452 TX RSE
Note : 2.4G WIFI 11N 40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1542.733	5.42	26.00	41.43	45.68	35.67	74.00	-38.33	peak
2	4469.214	7.53	33.55	42.41	46.00	44.67	74.00	-29.33	peak
3	4904.000	7.99	34.09	42.48	47.02	46.62	74.00	-27.38	peak
4	5746.982	9.72	34.85	41.82	46.82	49.57	74.00	-24.43	peak
5	7356.000	10.04	36.19	40.61	43.75	49.37	74.00	-24.63	peak
6	9808.000	10.85	37.79	37.46	40.07	51.25	74.00	-22.75	peak



8 Photographs

8.1 Test Setup

Refer to Setup Photos

8.2 EUT Constructional Details (EUT Photos)

Refer to EUT external and internal photos





9 Appendix


9.1 Appendix RSS247


1.6dB Bandwidth


Test Mode	Test Channel	Ant	EBW[MHz]	Limit[MHz]	Verdict
11B	2412	Ant1	9.150	≥ 0.5	PASS
11B	2437	Ant1	9.120	≥ 0.5	PASS
11B	2462	Ant1	9.120	≥ 0.5	PASS
11G	2412	Ant1	16.620	≥ 0.5	PASS
11G	2437	Ant1	16.590	≥ 0.5	PASS
11G	2462	Ant1	16.560	≥ 0.5	PASS
11N20SISO	2412	Ant1	17.820	≥ 0.5	PASS
11N20SISO	2437	Ant1	17.760	≥ 0.5	PASS
11N20SISO	2462	Ant1	17.760	≥ 0.5	PASS
11N40SISO	2422	Ant1	36.540	≥ 0.5	PASS
11N40SISO	2437	Ant1	36.600	≥ 0.5	PASS
11N40SISO	2452	Ant1	36.600	≥ 0.5	PASS






















2.Occupied Bandwidth


Test Mode	Test Channel	Ant	OBW[MHz]	Limit[MHz]	Verdict
11B	2412	Ant1	13.560	---	PASS
11B	2437	Ant1	13.470	---	PASS
11B	2462	Ant1	13.470	---	PASS
11G	2412	Ant1	16.920	---	PASS
11G	2437	Ant1	16.920	---	PASS
11G	2462	Ant1	16.920	---	PASS
11N20SISO	2412	Ant1	17.880	---	PASS
11N20SISO	2437	Ant1	17.850	---	PASS
11N20SISO	2462	Ant1	17.880	---	PASS
11N40SISO	2422	Ant1	36.360	---	PASS
11N40SISO	2437	Ant1	36.420	---	PASS
11N40SISO	2452	Ant1	36.420	---	PASS
















3.Maximum peak conducted output power


Test Mode	Test Channel	Ant	Power[dBm]	Limit[dBm]	Verdict
11B	2412	Ant1	17.58	<30	PASS
11B	2437	Ant1	17.77	<30	PASS
11B	2462	Ant1	17.51	<30	PASS
11G	2412	Ant1	18.07	<30	PASS
11G	2437	Ant1	18.17	<30	PASS
11G	2462	Ant1	18.1	<30	PASS
11N20SISO	2412	Ant1	17.72	<30	PASS
11N20SISO	2437	Ant1	18.82	<30	PASS
11N20SISO	2462	Ant1	18.23	<30	PASS
11N40SISO	2422	Ant1	18.59	<30	PASS
11N40SISO	2437	Ant1	18.67	<30	PASS
11N40SISO	2452	Ant1	18.4	<30	PASS

Pre-scan under all rate


Mode	802.11b							
Data Rate	1Mbps	2Mbps	5.5Mbps	11Mbps				
Power (dBm)	17.58	17.36	17.34	17.32				
Mode	802.11g							
Data Rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
Power (dBm)	18.17	18.15	18.13	18.12	18.10	18.08	18.06	18.04
Mode	802.11n(HT20)							
Data Rate	6.5Mbps	13Mbps	19.5Mbps	26Mbps	39Mbps	52Mbps	58.5Mbps	65Mbps
Power (dBm)	18.82	18.79	18.77	18.75	18.73	18.71	18.69	18.67
Mode	802.11n(HT40)							
Data Rate	13.5Mbps	27Mbps	40.5Mbps	54Mbps	81Mbps	108Mbps	121.5Mbps	135Mbps
Power (dBm)	18.67	18.66	18.64	18.62	18.61	18.59	18.57	18.55

Through Pre-scan, 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20). 13.5Mbps of rate is the worst case of 802.11n (HT40).


Maximum peak conducted output power_11B_2412_Ant1




Maximum peak conducted output power_11B_2437_Ant1




Maximum peak conducted output power_11B_2462_Ant1




Maximum peak conducted output power_11G_2412_Ant1




Maximum peak conducted output power_11G_2437_Ant1




Maximum peak conducted output power_11G_2462_Ant1




Maximum peak conducted output power_11N20SISO_2412_Ant1




Maximum peak conducted output power_11N20SISO_2437_Ant1




Maximum peak conducted output power_11N20ISO_2462_Ant1




Maximum peak conducted output power_11N40ISO_2422_Ant1



Maximum peak conducted output power_11N40SISO_2437_Ant1




Maximum peak conducted output power_11N40SISO_2452_Ant1










4.Maximum Peak power spectral density



Test Mode	Test Channel	Ant	PSD[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	2412	Ant1	-15.61	<8.00	PASS
11B	2437	Ant1	-15.16	<8.00	PASS
11B	2462	Ant1	-15.86	<8.00	PASS
11G	2412	Ant1	-18.5	<8.00	PASS
11G	2437	Ant1	-18	<8.00	PASS
11G	2462	Ant1	-18.32	<8.00	PASS
11N20SISO	2412	Ant1	-17.51	<8.00	PASS
11N20SISO	2437	Ant1	-17.43	<8.00	PASS
11N20SISO	2462	Ant1	-17.55	<8.00	PASS
11N40SISO	2422	Ant1	-18.04	<8.00	PASS
11N40SISO	2437	Ant1	-18.93	<8.00	PASS
11N40SISO	2452	Ant1	-17.9	<8.00	PASS























5.Band-edge for RF Conducted Emissions

Test Mode	Test Channel	Ant	Carrier Power[dBm]	Max. Spurious Level [dBm]	Limit [dBm]	Verdict
11B	2412	Ant1	7.350	-53.239	<-12.65	PASS
11B	2462	Ant1	6.740	-52.948	<-13.26	PASS
11G	2412	Ant1	1.790	-38.393	<-18.21	PASS
11G	2462	Ant1	0.570	-44.462	<-19.43	PASS
11N20SISO	2412	Ant1	-1.270	-47.750	<-21.27	PASS
11N20SISO	2462	Ant1	-1.780	-50.838	<-21.78	PASS
11N40SISO	2422	Ant1	-3.280	-38.941	<-23.28	PASS
11N40SISO	2452	Ant1	-3.610	-42.957	<-23.61	PASS











6.RF Conducted Spurious Emissions

Test Mode	Test Channel	StartFre [MHz]	StopFre [MHz]	RBW [kHz]	VBW [kHz]	Pref[dBm]	Max. Level [dBm]	Limit [dBm]	Verdict
11B	2412	30	10000	1000	3000	7.27	-26.500	<-12.73	PASS
11B	2412	10000	25000	1000	3000	7.27	-54.590	<-12.73	PASS
11B	2437	30	10000	1000	3000	7.34	-26.870	<-12.66	PASS
11B	2437	10000	25000	1000	3000	7.34	-55.070	<-12.66	PASS
11B	2462	30	10000	1000	3000	6.6	-28.350	<-13.4	PASS
11B	2462	10000	25000	1000	3000	6.6	-55.510	<-13.4	PASS
11G	2412	30	10000	1000	3000	1.76	-29.310	<-18.24	PASS
11G	2412	10000	25000	1000	3000	1.76	-55.250	<-18.24	PASS
11G	2437	30	10000	1000	3000	1.24	-31.110	<-18.76	PASS
11G	2437	10000	25000	1000	3000	1.24	-55.900	<-18.76	PASS
11G	2462	30	10000	1000	3000	1.33	-30.510	<-18.67	PASS
11G	2462	10000	25000	1000	3000	1.33	-54.910	<-18.67	PASS
11N20SISO	2412	30	10000	1000	3000	-1.51	-34.070	<-21.51	PASS
11N20SISO	2412	10000	25000	1000	3000	-1.51	-55.620	<-21.51	PASS
11N20SISO	2437	30	10000	1000	3000	-1.01	-33.490	<-21.01	PASS
11N20SISO	2437	10000	25000	1000	3000	-1.01	-55.640	<-21.01	PASS
11N20SISO	2462	30	10000	1000	3000	-1.67	-35.400	<-21.67	PASS
11N20SISO	2462	10000	25000	1000	3000	-1.67	-55.520	<-21.67	PASS
11N40SISO	2422	30	10000	1000	3000	-3.4	-36.310	<-23.4	PASS
11N40SISO	2422	10000	25000	1000	3000	-3.4	-55.750	<-23.4	PASS
11N40SISO	2437	30	10000	1000	3000	-3.21	-37.340	<-	PASS





SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch


Report No.: SZEM181000884602


Page: 125 of 143


								23.21	
11N40SISO	2437	10000	25000	1000	3000	-3.21	-55.360	<- 23.21	PASS
11N40SISO	2452	30	10000	1000	3000	-3.59	-37.180	<- 23.59	PASS
11N40SISO	2452	10000	25000	1000	3000	-3.59	-55.190	<- 23.59	PASS















RF Conducted Spurious Emissions_11G_2412_Ant1













RF Conducted Spurious Emissions_11G_2462_Ant1













RF Conducted Spurious Emissions_11N20SISO_2437_Ant1













RF Conducted Spurious Emissions_11N40SISO_2422_Ant1











RF Conducted Spurious Emissions_11N40SISO_2452_Ant1





- End of the Report -